



Perspex® 30 Year Guarantee Clear Cell Cast Acrylic Sheet

Clear Sheet

Lucite International guarantees that Clear Perspex® will not yellow and will retain high light transmission for 30 years.

1. The guarantee period of thirty years runs from the date of delivery of the sheet to the customer. The applicable guarantee is that which is valid on the day of delivery to the customer. This guarantee expires upon the de-installation of the first application or the wilful destruction or damage thereof, whichever occurs first.
2. The guarantee covers the quality of the sheet as delivered and in particular:
 - 2.1 The sheet must be appropriately stored and transported prior to fabrication and installation.
 - 2.2 High standards of workmanship shall be used in fabrication and installation and Lucite International will not be liable for any failure attributable to poor standards of such workmanship.
 - 2.3 The guarantee does not cover any failure attributable to causes not usually associated with the normal use of Perspex® acrylic sheet and in particular does not apply to harm caused by chemical agents, cleaning fluids, unsuitable sealants or decorative materials.
3. Lucite International must be given immediate notice of any complaint. Sufficient evidence of the complaint must be given to Lucite International and those authorised by it must be allowed adequate facilities to substantiate any complaint.
4. If any Perspex® shall be shown to Lucite International's satisfaction to have failed to comply with the said performance specifications within the stipulated time limit Lucite International shall replace the failed sheet with an equivalent amount of Perspex® or other suitable alternative sheet to be delivered free of charge by Lucite International to a delivery point to be nominated by the customer, but Lucite International shall under no circumstances be responsible for any other damage or loss howsoever arising whether directly or indirectly.
5. Lucite International gives no guarantee or warranty express or implied in relation to Perspex® acrylic sheet apart from the guarantee given herein.

6. This guarantee and all the terms thereof shall apply to all deliveries of Perspex® supplied by Lucite International until the guarantee is revoked by either of the parties.

Revocation may be effected by either party serving on the other notice in writing to that effect at any time.

7. Revocation shall not affect deliveries of sheet made prior to the date of revocation which shall continue to be fully covered by the terms of this guarantee.
8. If the customer shall bring any claim under this guarantee it shall produce documentary evidence to Lucite International's satisfaction that the sheet in question is Perspex® made by Lucite International.

Appendix

Outdoor ageing behaviour of Perspex® clear cast acrylic sheet.

1. Light transmission

The light transmission for clear Perspex® will not fall below 85% (test method: ASTM D 1003 when measured using a cleaned and polished flat sample of 1mm thickness taken from the exposed sheet).

2. The yellowness index of clear cast Perspex® will not be more than 10 after a period of 30 years, dependent on the application and surrounding environment. This value is measured using a cleaned and polished flat sample in accordance with DIN 5036.

LUCITE INTERNATIONAL 2009

Perspex® and Lucite® are registered Trade Marks owned by Lucite International UK Limited.